

Crockmeter Rubbing Fastness Tester HS-T101



Picture is for reference only

Application:

Crockmeter Rubbing Fastness Tester To determine the colour fastness of textiles to dry or wet rubbing. A pinned acrylic sample holder ensures rapid sample mounting and repeatability of results.

Feature:

- 1.Metal box, High-temperature baking coating, easy maintenance.
- 2.Electric motor, fitted with a pre-determined electronic counter for strokes up to 9999, experiment complete successfully, automatic stop.

Standards:

BS 1006- D02, ISO 105- X12/D02, AATCC 8/165, ASTM D6279, JIS L 0849 Type1 ,JIS L 0862 Type1

Key Specification:

Rubbing head diameter	16mm
Vertical pressure	9N±0.2N
Rubbing head track	104±3mm
Test speed	60±2 rpm
Power supply	AC 220V 50/60HZ
Dimension (L x W x H)	62 x 26 x 28cm
Weight	14kg
Control mode	Electronic control

Accessories:

Standard accessories	1box	Rubbing cloth
----------------------	------	---------------

	2pc	Sand paper
	2pc	Rings
	1pc	Power line
Optional accessories	Optional	Gray Scale for staining

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel/Whatsapp: +86-159 1008 1986

www.hssdgroup.com - e-mail: admin@hssdtest.com