

HST XJU ASTM D256 Digital Display Izod Pendulum Impact Testing Machine



Application:

This Impact Test is mainly used to measure the impact toughness of rigid plastic, reinforced nylon, fiberglass, ceramics, cast stone, insulation materials and other non-metallic materials. It is the ideal testing equipment in the chemical industry, scientific research institutes, universities and quality testing departments.

Standard:

ISO180, ASTM D256 and the equivalent.

Model	HSTXJUD-5.5T	HSTXJUD-22T
Standard	ISO180,ASTM D256	
Display	Touch screen	
Impact velocity	3.5m/s	
Impact energy	2.75J, 5.5J	11J, 22J
Precision	Angle (0.01 °) Energy (0.01J)	
Impact center distance	335mm	
Pendulum angle	150°	
Distance between striking edge and top surface of jaw	22.0mm±0.2mm	
Corner radius of striking edge	R=0.8mm±0.2mm	
Print out	Capacity. Angle, energy, etc.	
Power supply	AC220V, 50Hz	

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel/Whatsapp: +86-159 1008 1986

www.hssdgroup.com - e-mail: admin@hssdtest.com