

High Temperature Drying Oven HST-HTDO50AH



LCD Programmable controller (with timing function)

Provided for desiccation, torrefaction, wax-melting and sterilization in mining enterprises, laboratories and scientific research institutes.

Features

1. 304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable.
2. PID controller with over temperature alarm and timing function ensures precise and reliable control.
3. Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life.
4. Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan.
5. Independent over-temperature alarm system ensures experiments running safely

Specifications

Model	HST-HTDO50AH
Electrical Requirements	AC380V 50HZ
Temperature Range	AH series: RT+20℃ 400℃
Display Resolution	0.1℃
Temperature Stability	±0.5℃
Ambient Temperature	+5~40℃
Power Consumption	3250W
Chamber Volume	50L
Internal Dimension (W×D×H)mm	350×350×400
External Dimension (W×D×H)mm	890×700×920
Shelves	2(pcs)
Timing Range	0~5999min

Options

Micro printer RS485 connector

HST GROUP Co., LTD.

Jinan Hensgrand Instrument Co., Ltd.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Phone/WhatsApp: +86-159 1008 1986

www.hssdgroup.com - e-mail: admin@hssdtest.com