

Hot Air Oven



Picture just for reference

Product introduction:

It is applicable to testing, baking, drying and sterilization of non-volatile items used in industrial and mining enterprises, schools, medical and scientific research units.

A.Time setting: digital display, microcomputer temperature control system, high temperature precision.

B.Hot air circulation system : ventilator operational under high temperature, wind duct, working chamber evening temperature

C.Control system: intelligent temperature controller

D.Timing function: quick temperature recovery.

Specification and Technical parameters:

Article. No: 35

Working chamber dimension: H×W×D 340×320×320

External dimensions: H×W×D 620×530×490

No. 4915, Jingshi Road, Jinan, China

Tel:+86-15910081986

www.hssdgroup.com

Temperature range RT+10~250℃

Temperature fluctuation:±1℃

Tracking alert: +5℃

Temperature Control System:LED digital microscopic computer controller

Heating system:Fully independent systems, nickel-chromium alloy electric heating heaters

Circulatory system:Anti-high temperature and low noise motor

Security:Leakage, short circuit, over-temperature, motor overheating, over-current protection

Power: 800W

Supply Voltage: AC 220V 50Hz

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel: +86-159 1008 1986

www.hssdgroup.com - e-mail: admin@hssdtest.com