

HST JBWI-300B Computer Control Metal IZOD Impact Testing Machine



Picture just for reference

Application:

IZOD impact testing machine is used to test anti-impact performance of metal material under dynamic load to judge the nature of material under dynamic load. This machine is semi-automatic testing machine, easy to operate and high efficiency. They can make use of spare energy to raise pendulum automatically and be ready for next impact test, can carry out the impact test machinery continuously. It is widely used in the laboratory, metallurgy, manufacturing industry, etc.

Standards:

ISO R84, B·S 131 part 4, GB4158-84

Specifications:

MODEL	HST JBWI-300B
Impact energy (J)	150,300
Value of every grid (J)	0~300, 0~150

Moment of pendulum(N·m)	179.20
Impact velocity (m/s)	3.98
Distance between pendulum center and sample center (mm)	475
Specimen and distance of pendulum contact wires to the symmetry of gap(mm)	22±0.5
Pendulum preparing angle	135°
Pendulum apex angle	75±1°
Pendulum circle radius(mm)	0.5~1
The angle of sample front and pendulum underside	100±1°
Size of specimen (mm)	10×10×70~126mm square sample Φ11.43×71~127mm round sample
Power supply	3p 4-wire 380V 50Hz 250W or specified
Dimensions (mm)	1300×600×1340
Weight(KG)	450

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel: +86-159 1008 1986

www.hssdgroup.com - e-mail: admin@hssdtest.com